

SUN COOL
FABRICS


Sundance
Window Coverings

ATLAS


OPENNESS FACTOR 1%
SCREEN FABRIC



Atlas' horizontal lines evoke a modern yet inviting interior. Its densely woven construction provides the ultimate solar protection while blocking up to 99% of UV rays from entering and damaging interiors.




ROLLER SHADES




ROMAN SHADES



PANEL TRACKS




SKYLIGHT TRACKS




WHITE/GRAY

SC-A6-103



WHITE/WHITE

SC-A6-101



WHITE/TAN

SC-A6-102



FABRICATION METHODS

Cutting: Cold Cut, Ultrasonic, Crush Cut or Laser

Seaming / Hemming: Thermal, High-Frequency, Ultrasonic or Sewing.

PRODUCT SPECIFICATIONS

COMPOSITION	25% Polyester + 75% PVC
ROLL WIDTH	118"
ROLL LENGTH	33 yd
WEIGHT / YD ²	21.35 oz/yd ²
THICKNESS	.039" ± 5%
COLOR FASTNESS	8 Grade (SGS)
YARN COUNT	50*16
BREAKING STRENGTH	Warp 3824 N/5cm Weft 1224 N/5cm

CARE AND CLEANING

Remove dust with vacuum cleaner or compressed air. Do not scrub. Do not use solvents or any abrasive substance which might damage the coating on the fabric. Clean with a sponge or a soft brush dipped in soapy water using mild detergent. Rinse with clean water. Leave the shade down until completely dry. You can also rub the fabric very gently with a clean white pencil eraser to remove small stains.

CERTIFICATIONS, TESTS, AND WARRANTY

CALIFORNIA TITLE 19	OEKO-TEX® STANDARD 100	UL GREENGUARD GOLD	ROHS COMPLIANT	10 YEAR WARRANTY	ASTM G-21 & E-2180	NFPA® 701-TM
FLAME RETARDANT	FREE OF HARMFUL CHEMICALS	HEALTHY INDOOR AIR QUALITY	FREE OF HARMFUL METALS	QUALITY GUARANTEED	BACTERIA & FUNGAL RESISTANCE	FIRE RETARDANT

Sundance
Window Coverings